

Merten Maschinenbau u. Vertriebs GmbH • Puchgasse 9, A-1220 Vienna • P +43 1 2594648
 mm-office@merten.at • www.merten.at

Machine:	Overhead conveyor		
Short description:	OC/1120		
Drive: (dependent on length)	Conveyor up to 10m	AC-motor	1.100 Watt
	Conveyor up to 16m	AC-motor	1.500 Watt
	Conveyor up to 25m	AC-motor	2.200 Watt
	Conveyor up to 35m	AC-motor	3.000 Watt
Control system:	synchronous speed control via voltage generator, of the rotary printing press or stitching machine		
Tachometer signal output:	U max. 180 V DC		
Analog signal: from rotary printing press	UE 0-10 V DC I max. 15 mA		
Speed:	adjustable from 0 - 100 m/min (50 m/min at 50 Hz)		

Product stream thickness:	Total thickness max. 20 mm (pressed)
Paper weight:	up to the thickest kind of rotary printing paper
Product width:	min. 120 mm; max. 500 mm

Pressure rolls:	Pressure adjustable by springs
-----------------	--------------------------------

Monitoring device:	Switch off when product jams
--------------------	------------------------------

Input power:	1.100 up to 3.000 Watt (depending on conveying distance)
Voltage:	3 x 400 V AC + N + PE 50/60 Hz
Control voltage:	24.Volt
Nominal current:	depending on conveying distance
Primary fuse:	depending on conveying distance

Infeed height:	min. 150 mm
Delivery height:	min. 400 mm
Total length:	max. 35 m (at belt width 50mm)
Total width:	730 mm 840 mm (drive unit)
Total height:	dependent on order

Weight:	dependent on order
Color:	RAL 7035

Other colors, conveying heights and technical specifications, are available.
 IN-DAT-OC1120