

Machine:	Bump turn
Short description:	BTD/1120
Drive:	Feed conveyor AC-motor 370 Watt (2 x) Cross conveyor AC-motor 370 Watt (2 x)
Control system:	Depending on the version via analog speed signal or digital via bus connection
Analog signal:	UE 0-10 V DC
Digital signal:	Bus connection to central control cabinet
Speed:	adjustable from 0 - 100 m/min (50 m/min at 50 Hz)

Page count:	4 – 128 pages
Paper weight:	up to the thickest kind of rotary printing paper
Product width:	min. 115 x 125 mm max. 400 x 530 mm
Telescoping unit:	with two hand wheels
Bump plate adjustable:	fixed by clamp bolt

Air requirements:	Air consumption: 300 Norm l/min (24 Nm ³ /h) Air pressure: min. 4 bar; max. 7 bar
-------------------	---

Input power:	1.600 Watt
Voltage:	3 x 400 V AC + N + PE 50/60 Hz
Control voltage:	24 Volt
Nominal current:	7,4 Ampere
Primary fuse:	16 Ampere

Infeed height:	1.100 / 600 mm
Delivery height:	1.100 / 600 mm
Total length:	1.297 mm (without control cabinet) 1.536 mm (with control cabinet)
Total width:	1.135 mm (without control cabinet) 1.374 mm (with control cabinet)
Total height:	1.230 mm

Weight:	approx. 560 kg
Color:	RAL 7035

Other colors, conveying heights and technical specifications, are available. IN-DAT-BTD1120	
--	--