

Machine:	Overhead conveyor		
Short description:	OC/1120		
Drive:	Conveyor up to 10m	AC-motor	1.100 Watt
(dependent on length)	Conveyor up to 16m	AC-motor	1.500 Watt
	Conveyor up to 25m	AC-motor	2.200 Watt
	Conveyor up to 35m	AC-motor	3.000 Watt
Control system:	synchronous speed control via voltage generator, of the rotary printing press or stitching machine		
Tachometer signal output:	U max. 180 V DC		
Analog signal:	UE 0-10 V DC		
from rotary printing press	I max. 15 mA		
Speed:	adjustable from 0 - 100 m/min (50 m/min at 50 Hz)		

Product stream thickness:	Total thickness max. 20 mm (pressed)		
Paper weight:	up to the thickest kind of rotary printing paper		
Product width:	min. 120 mm; max. 500 mm		

Pressure rolls:	Pressure adjustable by springs		
-----------------	--------------------------------	--	--

Monitoring device:	Switch off when product jams		
--------------------	------------------------------	--	--

Input power:	1.100 up to 3.000 Watt (depending on conveying distance)		
Voltage:	3 x 400 V AC + N + PE 50/60 Hz		
Control voltage:	24.Volt		
Nominal current:	depending on conveying distance		
Primary fuse:	depending on conveying distance		

Infeed height:	min. 150 mm		
Delivery height:	min. 400 mm		
Total length:	max. 35 m (at belt width 50mm)		
Total width:	730 mm		
	840 mm (drive unit)		
Total height:	dependent on order		

Weight:	dependent on order		
Color:	RAL 7035		

Other colors, conveying heights and technical specifications, are available.			
IN-DAT-OC1120			