

Machine:	Rotary trimmer
Short description:	RT/1120 (Commercial) RT/2120 (Newspaper)
Drive:	Alignment AC-motor 120 Watt (2x) Knives AC-motor 2.200 Watt (2x) Belts AC-motor 1.500 Watt
Control system:	synchronous speed control via voltage generator, of the rotary printing press or stitching machine
Tachometer signal output:	U max. 180 V DC
Analog signal:	UE 0-10 V DC
from rotary printing press	I max. 15 mA
Speed:	adjustable from 0 - 120 m/min (60 m/min at 50 Hz)

Product stream thickness:	Total thickness max. 15 mm
Paper weight:	up to the thickest kind of rotary printing paper
Untrimmed product width:	min. 110 mm; max. 520 mm
Product alignment:	by vibrating belts adjustable during operation
Trimmed product width:	min. 100 mm; max. 500 mm
Slide adjustment:	with four hand wheels for alignment and knife slides, adjustable from both sides of the machine

Operation:	via two controller each left or right, adjustable from both sides of the machine
------------	--

Lower blade:	Ø 150 mm
Upper blade:	min. Ø 300 mm; max. Ø 308 mm
Paper waste each side:	min. 3 mm; max. 55 mm

Suction pipe:	Ø 100 mm (2x)
Suction device:	made by costumer
Exhaust power:	Air volume: 900 m ³ /Std
(per pipe)	Depression: 1.960 Pa (N/m ²) Air speed: 30 m/sec

Pressure rolls:	Pressure pneumatically adjustable
Air requirements:	Air consumption: minimal Air pressure: min. 4 bar; max. 7 bar

Noise level:	85dB (A) Maximum Conforming to DIN45635 paragraph 27
--------------	---

Monitoring device:	Switch off when product jams Switch off during emergency stop Switch off when the guard is open Knive section Switch off during loss of suction power
--------------------	---

Input power:	7.000 Watt
Voltage:	3 x 400 V AC + PE 50/60 Hz (other on request)
Control voltage:	24 Volt
Nominal current:	20 Ampere
Primary fuse:	32 Ampere

Infeed height:	800 mm
Delivery height:	800 mm
Total length:	1.500 mm
Total width:	1.480 mm
	1.600 mm (with hand wheels)
Total height:	1.100 mm

Weight:	approx. 750 kg
Color:	RAL 7035

Other colors, conveying heights and technical specifications, are available.
IN-DAT-RT1120-2120