

Machine:	Rotary trimmer		
Short description:	RTT/1140S	Double-stream trimmer (Commercial)	
	RTT/2140S	Double-stream trimmer (Newspaper)	
Drive trimmer:	Alignment	AC-motor	120 Watt (4x)
	Knives	AC-motor	2.200 Watt (4x)
	Belts	AC-motor	1.500 Watt (2x)
Control system:	Depending on the version via analog speed signal or digital via bus connection		
Analog signal:	UE 0-10 V DC		
Speed:	adjustable from 0 - 120 m/min (60 m/min at 50 Hz)		

Product stream thickness:	Total thickness max. 24 mm		
Paper weight:	Up to the thickest kind of rotary printing paper		
Untrimmed product width:	min. 145 mm; max. 520 mm		
Product alignment:	By vibrating belts, frequency adjustable		
Trimmed product width:	min. 135 mm; max. 500 mm		
Slide adjustment:	Two spindles each with four electro-magnetic couplings, adjustable via servo-motor on both sides of the machine		

Operation:	via control panel on top of the machine, adjustable from both sides of the machine		
------------	--	--	--

Lower blade:	Ø 152 mm		
Upper blade:	Ø 250 mm		
Paper waste each side:	min. 3 mm; max. 55 mm		

Suction pipe:	Ø 100 mm (4x)		
Suction device:	made by costumer		
Exhaust power: (per pipe)	Air volume: 900 m ³ /Std		
	Depression: 1.960 Pa (N/m ²)		
	Air speed: 30 m/sec		

Pressure rolls:	Pressure pneumatically adjustable		
Air requirements:	Air consumption: minimal		
	Air pressure: min. 4 bar; max. 7 bar		

Noise level:	85dB (A) Maximum Conforming to DIN45635 paragraph 27		
--------------	---	--	--

Monitoring device:	Switch off when product jams Switch off during emergency stop Switch off when the guard is open Switch off during loss of suction power
Input power:	14.000 Watt
Voltage:	3 x 400 V AC + PE 50/60 Hz (other on request)
Control voltage:	24 Volt
Nominal current:	33 Ampere
Primary fuse:	50 Ampere
Infeed height:	1.400 / 600 mm
Delivery height:	1.400 / 600 mm
Total length:	1.500 mm
Total width:	1.460 mm
	1.690 mm (with hand wheels)
Total height:	2.090 mm
Weight:	approx. 1.950 kg (without freestanding electrical cabinet)
Trimmer unit:	approx. 1.700 kg
Electrical cabinet:	approx. 450 kg
Color:	RAL 7035
Other colors, conveying heights and technical specifications, are available.	
IN-DAT-RTT1140S-2140S	