

The strapper of the SH/700 IG log stacker is set-up to use the following **standard** strapping material:

Material number Mosca	200147	pet-120-054-gr-1-g-406-2500-40ae	
Old material number Mosca	PET12010054-40AE	PET Strapping	
	Width of strapping belt	12,0mm (0,47")	0,47"
	Strap thickness	0,54mm (0,0213")	0,0213"
	Strap color	green	
	Tape length per roll	2.500m (98425,2")	98425,2"
	Roll diameter inner	406mm (15,98")	15,98"
	Roll diameter outside	590mm (23,23")	23,23"



The use of strapping material other than the one listed above may result in increased malfunctions or even machine damage.

Optionally, the following strapping material can also be used. However, this requires an adjustment of the strapping unit. For more information, please refer to the dedicated manual.

Material number Mosca	200115	pp-120-080-bl-1-g-406-2000-40ae	
Old material number Mosca	PP12250080-40AE	PP Strapping	
	Width of strapping belt	12,0mm	0,47"
	Strap thickness	0,8mm	0,0315"
	Strap color	black	
	Tape weight per meter	5,6g	0,0123lbs
	Tape length per roll	2.000m	78740,16"
	Roll diameter inner	406mm	15,98"
	Roll diameter outside	590mm	23,23"



For the use of other strapping material, the Mosca unit must be adjusted. Please check & perform directly with Mosca!

Technical specifications are subject to change without prior notice.

IN-DAT-SH700IG-STRAPPING