

|                            |                                                                               |
|----------------------------|-------------------------------------------------------------------------------|
| Machine:                   | Separation device                                                             |
| Short description:         | SS/1060                                                                       |
| Drive:                     | Basic unit AC-motor 250 Watt (2x)                                             |
| Control system:            | synchronous speed control via voltage generator, of the rotary printing press |
| Tachometer signal output:  | U max. 180 V DC                                                               |
| Analog signal:             | UE 0-10 V DC                                                                  |
| from rotary printing press | I max. 15 mA                                                                  |
| Speed:                     | adjustable from 0 - 80 m/min (50 m/min at 50 Hz)                              |
| Performance:               | 60.000 copies/hour                                                            |

  

|                                   |                                             |
|-----------------------------------|---------------------------------------------|
| Page count:                       | 4 - 48 pages                                |
| Paper weight:                     | max. 80 gram                                |
| Product width:                    | min. 150 mm; max. 485 mm                    |
| Side clearance of product stream: | max. $\pm 5$ mm, measured to machine center |
| Side product difference:          | min. 30 mm                                  |
| Clearance between products:       | min. 40 - 50 mm                             |
| Height adjustment:                | by means of central hand wheel              |

  

|                  |                                |
|------------------|--------------------------------|
| Input power:     | 4.000 Watt                     |
| Voltage:         | 3 x 400 V AC + N + PE 50/60 Hz |
| Control voltage: | 24 Volt                        |
| Nominal current: | 16 Ampere                      |
| Primary fuse:    | 25 Ampere                      |

  

|                  |          |
|------------------|----------|
| Infeed height:   | 800 mm   |
| Delivery height: | 800 mm   |
| Total length:    | 2700 mm  |
| Total width:     | 1.715 mm |
| Total height:    | 1.200 mm |

  

|         |                |
|---------|----------------|
| Weight: | approx. 600 kg |
| Color:  | RAL 7035       |

  

|                                                                                               |  |
|-----------------------------------------------------------------------------------------------|--|
| Other colors, conveying heights and technical specifications, are available.<br>IN-DAT-SS1060 |  |
|-----------------------------------------------------------------------------------------------|--|